

Penlon Prima 320 Anaesthesia System

ANAESTHESIA SOLUTIONS

- ◆ 8.4" TFT colour touchscreen
- ◆ Up to six ventilation modes
- ◆ Optional CO₂ and SpO₂ monitoring
- ◆ Integrated CO₂ absorber and bellows unit with ventilator interface
- ◆ Selectatec compatible back bar
- ◆ Switchable front facing common gas outlet



Penlon ◆

Penlon Prima 320 Anaesthesia System



All the features and options you need to configure a system to your exact specification

- ◆ 8.4" TFT colour touchscreen
- ◆ Up to six ventilation modes
- ◆ Optional CO₂ and SpO₂ monitoring
- ◆ Selectatec® compatible backbar (two stations)
- ◆ LED illuminated work spaces
- ◆ Large capacity drawer units
- ◆ Switchable front facing common gas outlet for open and closed circuit operation
- ◆ Integrated CO₂ absorber and bellows unit with ventilator interface
- ◆ GCX™ compatible aluminium uprights for additional accessory mounting
- ◆ Optional auxiliary O₂ outlet
- ◆ Up to three electrical outlets

2 Prima 320 Anaesthesia System

The Penlon Prima 320 is a versatile anaesthesia system providing the ideal solution for today's operating room.

Clinician-focused choices and benefits, including colour touchscreen display, up to six ventilation modes and optional CO₂ and SpO₂ monitoring.

System

The Prima 320 anaesthesia system has an integrated ventilator with up to six ventilation modes; CO₂ absorber with heater and large capacity absorbent canister; and a two station Selectatec™ compatible backbar.

Flow control and visualisation

The Prima 320 offers:

- Six conventional flow tubes for accurate control, particularly at low flow rates.
- A conventional control system with a mechanical anti-hypoxic device giving enhanced patient safety.
- 8.4" TFT colour touchscreen ventilator display with navigator wheel, push button control and audio/visual indicators.
- Switchable, front facing common gas outlet for open and closed circuit operation.
- Pipeline and cylinder pressure gauges.

Features and accessories

The territory-specific electrical power outlets can be used for ancillary medical devices. The mains power to internal components is supplemented by a backup battery able to maintain power for up to 90 minutes. A convenient and easily accessible O₂ outlet, for attaching an auxiliary flowmeter (order separately), is available as an option. Additional accessories can be mounted using the GCX™ compatible aluminium uprights.

Additional monitoring

For improved patient safety additional Sidestream CO₂ and SpO₂ monitoring options are also available.

System components

A versatile anaesthesia system, combining advanced features and value for money. The Prima 320 is easy to use and maintain, with superb performance.

1 Anaesthesia Ventilator

An easy to use, multifunction anaesthesia ventilator with 8.4" TFT touchscreen, designed for adult, paediatric and neonatal patient profiles. Standard specification includes up to six ventilation modes including advanced spontaneous support modes and electrical PEEP. The ventilator has integrated oxygen monitoring and spirometry, plus seamless integration with both the absorber and anaesthetic machine.

2 CO₂ Absorber

A high-performance absorber with a ventilator interface as standard that provides ventilator mode switching, triggered by the bag/ventilator control. The unit has a quick-release canister, and the main components are autoclavable. A heater unit is supplied as standard.

3 Sigma Delta Vaporizer

Award winning, high-performance market leader, offering multi-choice fill system options.

4 Flow Control

The Prima 320 comes with six conventional flow tubes to provide accurate control, particularly at low flow rates. The system has pipeline gas supply inputs for O₂, N₂O and Air; and backup cylinder supply inputs for O₂ and N₂O.

Maintenance and after-sales support

Penlon is committed to a successful, long-term relationship with all our customers. Our comprehensive warranty provides user peace of mind and after-sales support.

Additional services and warranties can be purchased to meet your particular needs.

